

SINGLE DOOR. B15

Art nr: **MV2255**

MOMEC
DOORS of SWEDEN



Fire rated hinge door special made for internal use in a maritime environment. Light duty door.

Fire class:	B15
Door leaf:	Made of steel and insulated with mineral wool. Standard is powder coating in RAL 9010
Thickness of door leaf:	38 mm
Frame:	Steel 1.5 mm
Hinges:	Stainless steel, 3 pcs
Striker plate:	Stainless steel
Sill cover:	Stainless steel
Max. clear opening:	W 1000 x H 2000 mm
Norsok door type code:	L1/L2



The door are tested according to IMO 2010 FTP Code

OPTIONS

- Laminated or pvc coated, stainless steel
- Kick/trolley plate made in stainless steel. H 300/800 mm
- Vision panel max W400 x H600 mm
- Panic device
- Kick-out panel 450 x 450 mm
- Ventilation grill 200 cm²
- Electric access control systems
 - Door open system
 - Hold open system
 - Door sensor



OPTION EXAMPLE

Vision panel, ventilation grill. Kick-out panel

DOOR SPAREPARTS

We provide all the necessary accessories for our doors.
Please contact our service department at:

Mail: service@momec.se | Phone: +46 734 42 55 87

Gaskets
Hinges
Handles
Lock Cases
Door Closers
Cylinders
Window Panels
Accessories

