

A-60  
MV4360G

**MOMEC**  
Doors of Sweden



## CHARACTERISTICS

### **A60 HINGED GASTIGHT**

**DOORLEAF (62 MM):** 1,0 mm galvanized steel with core of mineralwool (250kgs/m<sup>3</sup>)

**OPTION DOORLEAF FINISH:** Stainless steel, laminated, painted, pvc coated or offshore wet paint.

**FRAME:** 4,0 mm steel (bolted or welded). Silicone gasket four sides.

**OPTION FRAME FINISH:** Stainless steel or powder epoxy coated (painted) or offshore wet paint.

**HINGES:** Three pcs of stainless steel with grease nipple.

**STRIKERPLATE:** Stainless steel (1,0 mm)

**SILL COVERPLATE:** Stainless steel (option) (1,0 mm)

**LOCKING:** Assa Abloy, Schwepper, VingCard, Dorma.

**MAX. CERTIFIED CLEAR OPENING:** 1170 x 2000 mm (W x H)

**OPTION:** Window and hoseport

Reinforcement for holder and closer at upper and lower part of doorleaf.

**Momec AB**

Stråkenvägen 2 • SE-565 76 Bottnaryd • Phone +46 36 203 00  
www.momec.com • info@momec.com